

- ◆ 5 years Manufacturer Warranty
- ◆ Warranty on Electrical Performance: 10 years 90% + 25 years 80% of power output

### Manufacturing

- ◆ Original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing.
- ◆ Comprehensive module power testing.

### Performance

- ◆ Higher module efficiency and compact size. Weakened hot-spot effect, lower module failure rate and increased stability by shingle-tech.
- ◆ Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ◆ IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



# SOL-SH170

## Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m<sup>2</sup>, TC=25°C

Nominal Power	170W
Cell Type	Monocrystalline
Cell Efficiency	22%
Maximum Power Current (Impp)	8.33A
Maximum Power Voltage (Vmpp)	20.41V
Open-circuit Voltage (Voc)	24.26V
Short-circuit Current (Isc)	8.83A
Maximum System Voltage	500V
Output Tolerance	±3%
Cable	700mm / 2.5mm <sup>2</sup>
Connector Type	MC4 / MC4 Compatible
Module Structure	Aluminum Frame / Glass / EVA / Backsheet
Junction box rating	IP67
Diode	•
Working Temperature	-40~+80°C

## Packaging

Module Dimensions	1230*670*30mm
Module Weight	8.4kg
Package	Single Package
Pieces per Pallet	30pcs
Gross Weight per Pallet	308kg
Pallet Dimensions	1260*1100*850mm

*Guaranteed Performance*

**5 Years Manufacturers Warranty**

**Sunshine Solar Limited**

Unit 30, Ashwellthorpe Industrial Estate, Ashwellthorpe  
Norwich, Norfolk NR16 1ER

Tel: +44 (0)1508 488188 - Fax: +44 (0)1508 488288

www.sunshinesolar.co.uk - support@sunshinesolar.co.uk